

Asiantool Specification

Model	Conductor	Current Amp.	Voltage AC/DC V	Max.Freq. MHZ	Max. RPM	Operating Temp. Max/Min °C	Rotating Torque (gm-cm)	Insulation Resistance
A1M	1	10		200	3600	60/-30	35	
A1MT	1	10		200	3600	60/-30	35	
A1M2	1	20		200	2000	60/-30	50	
A1M5	1	50		200	1800	60/-30	70	
A1HH	1	250		200	1200	60/-30	250	
A1H25S	1	250		200	1200	60/-30	250	
A125PS	1	250		200	1200	60/-30	250	
A1H35S	1	350		200	800	60/-30	300	
A1H50PS	1	500		200	300	60/-30	700	
A1H65S	1	650		200	200	60/-30	1000	
A1H65PS	1	650		200	200	60/-30	1000	
A1H90PS	1	900		200	200	60/-30	1100	
A1H150PS	1	1500		200	100	60/-30	2000	
A1H300PS	1	3000		200	60	60/-30	3000	
A1H500FS	1	5000		200	50	60/-30	4000	
A1H750FS	1	7500		200	50	60/-30	6000	
A2S	2	4	250	200	2000	60/-30	75	> 25MΩ
A3S	3	4	250	200	1800	60/-30	100	> 25MΩ
A3S-W	3	4	250	200	1800	60/-30	100	> 25MΩ
A4S-W	4	4	250	200	1200	60/-30	150	> 25MΩ
A2H	2	30	250	200	1800	60/-30	200	> 25MΩ
A3M	3	30/4	250	200	1800	60/-30	200	> 25MΩ
A3M-W	3	4	250	200	1800	60/-30	200	> 25MΩ
A3H	3	30	250	200	1200	60/-30	400	> 25MΩ
A4H	4	30/4	250	200	1200	60/-30	400	> 25MΩ
A6H	6	30/4	250	100	300	60/-30	700	> 25MΩ
A8H	8	30/4	250	100	200	60/-30	1000	> 25MΩ
A1030	10	30/4	250	100	100	60/-30	1500	> 25MΩ
A1230	12	30/4	250	100	60	60/-30	2000	> 25MΩ
A1430	14	30/4	250	100	60	60/-30	2000	> 25MΩ
A2H6	2	60	250	200	600	60/-30	400	> 25MΩ
21005W	7	100/4	250	100	100	60/-30	1500	> 25MΩ
A2HV	2	30	500	100	400	60/-30	400	> 50MΩ
A3HV	3	30	500	100	300	60/-30	700	> 50MΩ
A4HV	4	30	500	100	200	60/-30	1000	> 50MΩ
A5HV	5	30	500	100	100	60/-30	1500	> 50MΩ
A6HV	6	30	500	100	60	60/-30	2000	> 50MΩ
A7HV	7	30	500	100	60	60/-30	2000	> 50MΩ